

ARTIC PLUS

FEATURES

- ✓ Filters manufactured from polyester resin and fiberglass.
- ✓ Filtrating bed depth: 1.2m.
- ✓ Filter color: Ivory.
- ✓ Black top lid with screws from 650 up 950 models and top Ø400 manhole in 1050 and 1200 models.
- ✓ Fitted with 1" arm collectors.
- ✓ Maximum pressure 2.5 bar.
- ✓ Maximum temperature: 50°C.
- ✓ Manual 1" water drain in 650 up to 950 models and sand drain of 2 ½" in 1050 and 1200 models.
- ✓ Lateral sand discharge of Ø200mm on all models.

OPTIONAL

- ✓ Sight-glass.
- ✓ Nozzle plate in 650 to 1200 models.
- ✓ Ø400mm lateral manhole in 1050 and 1200 models.
- ✓ Internal coating of vinylster resin for ozone treatments.



FILTER DETAILS




▪ Nozzle plate



▪ Optional sight-glass



▪ Cone diffuser



▪ Fitted with 1" collector arms



▪ Sand drain 2 ½"



▪ Black top lid with screws



▪ Top Ø400 manhole on 1050 and 1200 models

TECHNICAL DATA

PACKAGING

Code	Model (mm)	Connections (mm/inch)		Filtering velocity (m ² /h/m ²)	Filtration Area (m ²)	Flow (m ³ /h)	Maximum pressure (bar)	Net weight (kg)	D (mm)	H (mm)	M (mm)	N (mm)	Units per pallet	Box dimension (cm)
		mm	inch											
36053-000	650	50	1 ½"	50	0.33	17	2.5	75	680	1900	775	125	1	85x85x200
36054-000	800	63	2"	50	0.5	25	2.5	80	830	1950	685	230	1	95x95x205
41373	950	75	2 ½"	50	0.7	36	2.5	119	970	1960	655	270	1	110x110x210
36055	1050	90	3"	50	0.86	44	2.5	140	1090	2145	610	270	1	110x110x225
36056	1200	110	4"	50	1.13	57	2.5	210	1250	2170	665	270	1	135x135x225

MEDIA WEIGHT

Code	Sand (0.4-0.8) (kg)	Gravel (1-2mm) (kg)
36053-000	470	100
36054-000	660	165
41373	1015	260
36055	1240	320
36056	1665	410

